

Fibre Drum Specification Sheet

CONFORMS WITH REGULATIONS

NMFC:	Item 291
UN:	1G/Y60/S

NOMINAL DIMENSIONS

Inside Diameter:	9-9/16"
Inside Height:	8-1/4"
Outside Height:	8-3/4"
Tare Weight (approx):	1.7#
Net Packing Weight:	150#

NOMINAL CAPACITY

U.S. Gallons:	2.5
----------------------	-----

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting minimum thickness requirements of 600 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	N/A		
Barrier:	N/A		
Bottom:	.120"/800# PSI Heading (Thickness/Test)		
Chime Band Top:	N/A	Width:	N/A
Chime Band Bottom:	N/A	Width:	N/A
Closure:	N/A		
Cover Type:	Fibre - .120"/800# PSI Heading (Thickness/Test)		
Gasket:	N/A		
Fittings:	N/A	Diaphragm:	N/A
Additional Construction Information:	N/A		

TREATMENT


Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

Special Instructions: Certificate stamp on sidewall with customer specification number below

MARKINGS

Mfg Certificate Stamp:	150#
-------------------------------	------

NOTE: All dimensions listed on the above drum are nominal. Kraft paper is subject to change with variances in relative humidity. Diameters can vary $\pm 1/16"$. Height tolerances can vary $\pm 1/4"$ per ft. of drum sidewall. Weight tolerances can vary $\pm 5\%$. All thicknesses and other dimensions are nominal unless otherwise stated.

DISTRIBUTED BY:	REF NO.:
	DWG31368
DESCRIPTION:	
2.5 Gallon Kraft Fiber OH All-Fi Drum with Slip Cover	

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.