

**CONFORMS WITH REGULATIONS**

<b>NMFC:</b>	Item 291
<b>UN:</b>	1G/X71/S

**NOMINAL DIMENSIONS**

<b>Inside Diameter:</b>	14-1/2"
<b>Inside Height:</b>	23-1/2"
<b>Outside Height:</b>	24"
<b>Tare Weight (approx):</b>	5.6#
<b>Net Packing Weight:</b>	150#

**NOMINAL CAPACITY**

<b>U.S. Gallons:</b>	20
----------------------	----

**CONSTRUCTION – (All thickness and weights reflect minimum requirements)**

<b>Sidewall:</b>	Convolutely wound paperboard meeting minimum thickness requirements of 600 PSI Mullen.		
<b>Sidewall Adhesive:</b>	Sodium Silicate Between Each Lamination		
<b>Lining:</b>	N/A		
<b>Barrier:</b>	N/A		
<b>Bottom:</b>	.120"/800# PSI Heading (Thickness/Test)		
<b>Chime Band Top:</b>	N/A	<b>Width:</b>	N/A
<b>Chime Band Bottom:</b>	N/A	<b>Width:</b>	N/A
<b>Closure:</b>	N/A		
<b>Cover Type:</b>	Fibre - .120"/800# PSI Heading (Thickness/Test)		
<b>Gasket:</b>	N/A		
<b>Fittings:</b>	N/A	<b>Diaphragm:</b>	N/A
<b>Additional Construction Information:</b>	N/A		

**TREATMENT**

<b>Exterior Finish:</b>	Plain Kraft	<b>Paint or Skin Color:</b>	N/A
<b>Print:</b>	N/A		
<b>Print Color:</b>	N/A		
<b>Poly Bag:</b>	N/A	<b>Bag Option:</b>	N/A
<b>Misc. Treatments:</b>	N/A		

**Special Instructions:** N/A**MARKINGS**

<b>Mfg Certificate Stamp:</b>	150#
-------------------------------	------

NOTE: All dimensions listed on the above drum are nominal. Kraft paper is subject to change with variances in relative humidity. Diameters can vary  $\pm 1/16"$ . Height tolerances can vary  $\pm 1/4"$  per ft. of drum sidewall. Weight tolerances can vary  $\pm 5\%$ . All thicknesses and other dimensions are nominal unless otherwise stated.

DATE: 12/15/2020

**DISCLAIMER**

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



ipeline Packaging

REF NO.:

DWG10191

DESCRIPTION:

20 GAL\_KRAFT\_FIBER\_OH  
DRUM\_ROCON\_\_1G/X71/S\_@27 PALLET