


<sup>D</sup>  
Per C.M.A. Standard  
"T" = 0.798/0.784 Dia.  
"E" = 0.714/0.700 Dia.

Seal Type No. 1: Valve Seal (The most efficient provided bottle has proper "I" dimension)  
Seal Type No. 2: Land Seal ("I" dimension of bottle less critical than above)  
Dimensions marked \* are an average of two measurements taken 90° apart.  
GENERAL TOLERANCE NOT SHOWN OTHERWISE: ± .008

- BOTTLE NOTES:**
- 1) Thread: 8 Pitch, Per S.P.I. Standard.
  - 2) Diameters must be concentric within .015" T.I.R.
  - 3) All Dimensions are in inches unless otherwise indicated.

**Application Torque:**  
**10 Inch/lbs.**

<p align="center"><b>DISCLAIMER</b></p> <p>THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.</p>	<p>DISTRIBUTED BY: </p>	<p>REF NO.:</p> <p align="center"><b>DWG31390</b></p>
	<p>DESCRIPTION:</p> <p align="center">20-410 White LDPE Plastic Turret Spout, 2.5mm Orifice, PS149</p>	