

Specifications

11111	41 10 11/4 00 10
UN Mark(s)	1H2/X120/S
Nominal Capacity	30 gal
Nominal O.D. (A)	21.5 inches
Opening I.D.	19.2 inches
Overall Height (B)	30.1 inches
Body Height	29.8 inches
Taper Height	23.3 inches
Nest Height	5.5 inches
Chime Height	0.480 inches
Total Weight	15.2 lbs
Body Weight	11.3 lbs
Min. Wall Thickness	0.090 inches

Body Construction	Extrusion blow molded
Resin Type	HDPE / GB1 Resin
Body Color	Black
Cover Type	Plastic, FIG, Plain
Cover Color	Black
Closing Ring	Steel Exterior Lever-Lok 16ga
Special Instructions	None
Design Notes	Drums are fully nestable without airlocking. Recycle symbol embossed on bottom.
Filling Temperature	Maximum filling temperature 160°F. When filled at this maximum temperature,
	drums should be allowed to cool to ambient prior to stacking.
	Drums filled at elevated temperatures should be vented properly to prevent
	vacuum formation within the drum which can compromise stacking capability.

DISTRIBUTED BY:

ipeline Packaging

REF NO.:

DWG31353

<u>DISCLAIMER</u>
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DESCRIPTION:

30 Gallon HDPE OH Nestable Drum, with Cover and Lever Lock