Finish / Item Type
NATURAL Finished

Revision 09/10/2019

Specification

Plastics-Workcenter

- 1 Weight: 1125 1175 Grams
- 2 Container Markings and Bottle Finish: Visually check 100%
- 3 Material LP5100 or CP50100 HDPE with .5 % of UVI

QA

1 Wall Thickness: Top: .039" Min.

Middle: .040" Min. Bottom: .039" Min.

'S': .115" - .135"

Planarity: .010 Max.

3 Leak Torque 70MM: 175-185 in. lbs. Leak Torque 22MM: 25-30 in-lbs.

- 4 Stripping Torque for Closure Strength: 192 in. lbs. min.
- 5 Overall Height: 14.09 14.34"

Width: 10.06 - 10.31" Length: 11.04 - 11.29"

Overflow Capacity 5.1 Gal. Min.

- 6 UN TEST See UN/DOT standards for instructions.
 - A. 24 hour freezer drop test.
 - B. 1 hour vibration test
 - C. Hydrostatic pressure test
 - D. Dynamic Compression test / stack test
 - E. Leakproofness test

No single container is expected to pass more than one of these tests.

UN#: Container to be recertified annually.

- 7. The 7945-738-060 is 112pcs./bundle.
- 8. The 22mm vent stem DOES NOT have a hole. The 70mm neck ships with a white dust cap on and the 22mm has an F-217 Liner in the 22mm cap.

'H' .55" - .65"

9. Ships on a 48" x 40" Grade A Reconditioned Pallet.

DISTRIBUTED BY:

REF NO.:

ipeline Packaging

DWG30219

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DESCRIPTION:

5 Gallon Natural HDPW Square TH Pail