

# 16.5 gal Open Head Kraft Fiber Drum

## CONFORMS WITH REGULATIONS

NMFC:	Item 291
UN:	1G/X60/S

## NOMINAL DIMENSIONS

Inside Diameter:	14"
Inside Height:	24-7/8"
Outside Height:	25-7/8"
Tare Weight (approx):	6.9#
Net Packing Weight:	225#

## MARKINGS

Mfg Certificate Stamp:	225#
------------------------	------

## NOMINAL CAPACITY

U.S. Gallons:	16.5
---------------	------

## CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting or exceeding minimum thickness requirements of 700 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	N/A		
Barrier:	N/A		
Bottom:	.120"/1000# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel	Width:	Standard
Chime Band Bottom:	Galvanized Steel	Width:	Standard
Closure:	Galvanized Steel		
Cover Type:	26 Ga Steel – Interlocking		
Gasket:	N/A		
Fittings:	N/A	Diaphragm:	N/A
Additional Construction Information:	N/A		

## TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

Special Instructions: N/A

## DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DESCRIPTION: