

CONFORMS WITH REGULATIONS

NMFC:	Item 296 – Liquid 2A
UN:	1G/Y200/S

NOMINAL DIMENSIONS

Inside Diameter:	21-1/2"
Inside Height:	37-1/16"
Outside Height:	38-1/16"
Tare Weight (approx):	18.1#
Net Packing Weight:	600#

NOMINAL CAPACITY

U.S. Gallons:	55
---------------	----

CONSTRUCTION – (All thickness and weights reflect minimum requirements)

Sidewall:	Convolutely wound paperboard meeting minimum thickness requirements of 1200 PSI Mullen.		
Sidewall Adhesive:	Sodium Silicate Between Each Lamination		
Lining:	Heavy Duty Polyethylene		
Barrier:	N/A		
Bottom:	.240"/1500# PSI Heading (Thickness/Test)		
Chime Band Top:	Galvanized Steel with Stainless Steel Overlay	Width:	Standard
Chime Band Bottom:	Galvanized Steel	Width:	Wide
Closure:	Galvanized Steel		
Cover Type:	Plastic		
Gasket:	Urethane		
Fittings:	2" & 3/4" Plugs	Diaphragm:	Removed
Additional Construction Information:	N/A		

TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color:	N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	N/A
Misc. Treatments:	N/A		

Special Instructions: Certificate stamp on sidewall with customer specification number above

MARKINGS

Mfg Certificate Stamp:	600#
------------------------	------

NOTE: All dimensions listed on the above drum are nominal. Kraft paper is subject to change with variances in relative humidity. Diameters can vary +/- 1/16". Height tolerances can vary +/- 1/4" per ft. of drum sidewall. All thicknesses and other dimensions are nominal unless otherwise stated.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG30167

DESCRIPTION:

55 Gallon Fiber Drum