

## NOMINAL DIMENSIONS

Inside Diameter:	14"
Inside Height:	14-7/8"
Outside Height:	15-3/8"
Tare Weight (approx):	5#
Net Packing Weight:	150#

### NOMINAL CAPACITY

U.S. Gallons: 13.1

CONSTRUCTION - (All thickness and weights reflect minimum requirements)

The first the tricking and weights remote minimum equilibrium.					
Sidewall:	Convolutely wound paperboard meeting minimum thickness requirements of				
	600 PSI Mullen.				
Sidewall Adhesive:	Sodium Silicate Between Each Lamination				
Lining:	N/A				
Barrier:	N/A				
Bottom:	.120"/800# PSI Heading (Thickness/Test)				
Chime Band Top:	N/A	Width:	N/A		
Chime Band Bottom:	N/A	Width:	N/A		
Closure:	N/A				
Cover Type:	Fibre120"/800# PSI Heading (Thickness/Test)				
Gasket:	N/A				
Fittings:	N/A	Diaphragm:	N/A		
Additional Construction					
Information:	N/A				

## TREATMENT

Exterior Finish:	Plain Kraft	Paint or Skin Color	: N/A
Print:	N/A		
Print Color:	N/A		
Poly Bag:	N/A	Bag Option:	WA
Misc. Treatments:	N/A		

# Special Instructions: N/A

#### MARKINGS

Mfg Certificate Stamp: 150#

NOTE: All dimensions listed on the above drum are nominal. Kraft paper is subject to change with variances in relative humidity. Diameters can vary ±1/16". Height tolerances can vary ±1/4" per ft. of drum sidewall. Weight tolerances can vary ±5%. All thicknesses and other dimensions are nominal unless otherwise stated.

**DISCLAIMER** 

DISTRIBUTED BY: REF NO.: ipeline Packaging

DWG30610

**DESCRIPTION:**