


<b>Regulatory Information:</b>  un 1H2/X65/S (Test Report P205)  un 1H2/Y100/S (Test Report P204)  un 1H2/Y60/S (Test Report P272) * (see special note 7)		<b>Bill of Materials:</b>  <b>Body:</b> O-15, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)  <b>Cover:</b> Plain or Bung & Vent, HDPE. The B & V design has a 2" and a 3/4" NPS bung, with a vented 3/4" being available as an option. (NPS = National Pipe Straight thread)  <b>Lockband:</b> Side lever (SLL), Bolt or plastic.		<b>Product Illustration:</b>  	
<b>Nominal Capacity:</b> 15.0 U.S. Gallons	<b>Outage:</b> 1.0 U.S. Gallons	<b>Opening I.D.:</b> 13.7 inches	<b>Total Weight:</b> 8.7 lbs.		
<b>Maximum Capacity:</b> 16.0 U.S. Gallons	<b>Outage %:</b> 6.7 %	<b>Nominal O.D.:</b> 14.9 inches	<b>Body Weight:</b> 7.0 lbs.		
<b>Export Cubes:</b> 3.06 cu. ft.	<b>Overall Height:</b> 27.8 inches	<b>Taper Height:</b> 15.8 inches	<b>Nesting Height:</b> 10.9 inches		
<b>Min. Blocking Diameter:</b> 13.0 inches	<b>Body Height:</b> 27.4 inches	<b>Min. Wall Thickness:</b> 0.105 inches	<b>Chime Height:</b> 0.525 inches		
<b>Special Notes:</b> 1) Maximum filling temperature ~150°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 750 lbs. each. May be stacked two (2) drums high per pallet with slip sheet of plywood between layers of drums with top load not exceeding the specified limit. Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Drums are fully nestable without airlocking. 5) Recycle symbol embossed on bottom. 6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 7) Available with plastic lockband only at Y60 level.					

**DISCLAIMER**

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG30612

DESCRIPTION:

15 Gallon Blue Plastic Open Head Drum