## 30 gal Open Head Blue Plastic Drum

Product Specification Numb		Product Name: OS-30	
Regulatory Information:	Bill of Materials:	Product Illustration:	
un 1H2/X150/S¹ (Test Report P245) un 1H2/X125/S² (Test Report P244)	Body: OS-30, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)		
un 1H2/Y180/S³ (Test Report P246)	Cover: Plain or Bung & Vent, HDPE.		
UN 1H2/Y260/S (Test report P402, note 9)	The B & V design has a 2" and a 34" NPS bung, with a vented 34" being		
UN 1H2/Y100/S (Test report P236)	available as an option. (NPS = National Pipe Straight thread)		
	Lockband: Side lever (SLL), Bolt and plastic.		
Nominal Capacity:	Outage:	Opening I.D.:	Total Weight:
30.0 U.S. Gallons	2.2 U.S. Gallons	17.5 inches	14.6 lbs.
Actual Capacity:	Outage %:	Nominal O.D.:	Body Weight:
32.2 U.S. Gallons	7.3 %	19.3 inches	11.3 lbs.
Export Cubes:	Overall Height:	Min. Wall Thickness:	Chime Height:
6.05 cu. ft.	29.4 inches	0.125 inches	0.530 inches
Min. Blocking Diameter:	Body Height:	Mid Panel Height:	
18.7 inches	29.1 inches	11.4 inches	

## Special Notes:

- Maximum filling temperature 150 F. When filled 5) at this recommended maximum filling temperature drums should be allowed to cool to 6) ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.
- Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.
- 3) Handle with parrotbeak, side grabber, and sling.
- 4) Recycle symbol embossed on bottom.

- Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.
- Manufactured at the following locations:
  - Houston, with heavyweight cover
  - <sup>2</sup> Houston, with lightweight cover
  - Houston, Hazleton and Lockport with lightweight cover
- Lockport weight is body / assembled 10.7/14.0 lbs nominal
- Hazleton weight is body / assembled 10.4/13.7 lbs nominal
- Available only from Lockport with total drum weight 15.3 lbs.

## DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTR	IBU	TED	BY:
ı			

ipeline Packaging

DESCRIPTION:

REF NO.: