


Regulatory Information: un 1H2/X150/S (Test Report P249) un 1H2/Y250/S (Test Report P250)		Bill of Materials: Body: OS-55, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Cover: Plain or with 2 x 2" NPS bungs, HDPE. Vented bungs are available as an option. (NPS = National Pipe Straight thread) Lockband: Side lever (SLL) or Bolt		Product Illustration: 	
Nominal Capacity: 55.0 U.S. Gallons	Outage: 1.4 U.S. Gallons	Opening I.D.: 19.3 inches	Total Weight: 20.0 lbs.		
Actual Capacity: 56.4 U.S. Gallons	Outage %: 2.5 %	Nominal O.D.: 22.9 inches	Body Weight: 16.8 lbs.		
Export Cubes: 10.08 cu. ft.	Overall Height: 36.8 inches	Min. Wall Thickness: 0.135 inches	Chime Height: 0.480 inches		
Min. Blocking Diameter: 21.1 inches	Body Height: 36.5 inches	Mid Panel Height: 10.3 inches			

Special Notes:

- 1) Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.
- 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1300 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.
- 3) Handle with parrotbeak, side grabber, and sling.
- 4) Recycle symbol embossed on bottom.
- 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG30613

DESCRIPTION:

55 Gallon Blue Plastic Open Head Drum