



NOMINAL DIMENSIONS

| | |
|-----------------------|-----------------|
| Inside Diameter: | 22.1/2" |
| Inside Height: | 32 1/2" minimum |
| Outside Height: | 33" Minimum |
| Tare Weight (approx): | 42-50 lbs |

NOMINAL CAPACITY

| | |
|---------------|----|
| U.S. Gallons: | 55 |
|---------------|----|

CONSTRUCTION

| | |
|----------------------|--|
| Top mm thickness: | 1.1 mm minimum |
| Body mm thickness: | .9 mm minimum |
| Bottom mm thickness: | .9 mm minimum |
| Closure: | 12 guage ring with 5/8" bolt and jam nut |
| Cover Gasket: | 7/16" Round Sponge Rubber |

FITTINGS


| | | | | | | | |
|---------------|------|------------------|-------|----------------|-------|-------------------|--------------------|
| Fitting Size: | 2" | Flange Material: | Steel | Plug Material: | Steel | Position in Drum: | Cover 12:00 |
| Fitting Size: | 3/4" | Flange Material: | Steel | Plug Material: | Steel | Position in Drum: | Cover 6:00 |
| Fitting Size: | 2" | Flange Material: | Steel | Plug Material: | Steel | Position in Drum: | Bottom third panel |
| Fitting Size: | | Flange Material: | | Plug Material: | | Position in Drum: | |

TREATMENT

| | |
|--|-------------------------|
| Paint Color: - Lid/Top/Center/Bottom | White/Black/Black/Black |
| Ext. / Decoration / Labels | None |
| Linning / Inserts: | None |
| Special Instructions: Must use 2" Converter Bungs for side bung fitting. | |
| | |
| | |

MARKINGS

| | |
|-----------------|-----------------|
| UN EMBOSSMENTS: | UN 1A2/Y1.2/100 |
|-----------------|-----------------|

| | |
|---|--|
| DISTRIBUTED BY: | REF NO.: |
|  | DWG30440 |
| DESCRIPTION: | 55 Gallon Black OH Steel Reconditioned Drum with White Cover |

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.